

## MG 6/5 I-D/AE-Y

### + DIESEL ENGINE DRIVEN THREE-PHASE GENERATOR / OUTPUT POWER 6 KVA THREE-PHASE AND 5 KVA SINGLE-PHASE

---

<b>Gen Set Features</b>	<ul style="list-style-type: none"><li>+ Low oil pressure and battery charger warning lights</li><li>+ 12V built-in battery with electric start</li><li>+ Fuel level indicator</li><li>+ 1 x 400 V - 50 Hz three-phase outlet</li><li>+ 1 x 230 V - 50 Hz Single-phase outlet protected by circuit breaker</li><li>+ Earth Leakage Circuit Breaker (ELCB)</li><li>+ Voltmeter</li></ul>
<b>Gen Set Options</b> (available as factory options)	<ul style="list-style-type: none"><li>+ 60 Hz version</li><li>+ Versions with different voltages</li><li>+ AMF panel for auto start operation (AA model)</li></ul>
<b>Accessories on Request</b>	<ul style="list-style-type: none"><li>+ Trolley: two-wheels and handles</li></ul>
<b>Noise Level</b>	+ LWA 99 (74 dB at 7m)
<b>AC Generator - 50 Hz</b>	<ul style="list-style-type: none"><li>+ Type Gen Set asynchronous self-excited and self-protected</li><li>+ Three-phase Power (stand by) 6 kVA - 400 V</li><li>+ Single-phase Power (stand by) 5 kVA - 230 V</li><li>+ Power Factor 0,8</li></ul>
<b>Diesel Engine 3000 rpm</b>	<ul style="list-style-type: none"><li>+ Type <b>Yanmar L100 AE</b> - 1 cyl. - 10 HP (7,4 kWm) - 406 cm<sup>3</sup></li><li>+ Fuel diesel</li><li>+ Cooling system air</li><li>+ Starting system electric (and manual)</li><li>+ Fuel tank capacity 5,5 l</li><li>+ Fuel consumption @ 75% 1,7 l/h</li></ul>
<b>Other Features</b>	<ul style="list-style-type: none"><li>+ Insulation Class F</li><li>+ Mechanical Protection IP 23</li><li>+ Dimensions (L x W x H) 920 x 460 x 570 mm</li><li>+ Net Weight 135 kg</li></ul>

---

---

### + MG 6/5 I-D/AE-Y

